



← Back to results cooler smart device holder;

## Solar powered cooler for smart device

### Abstract

A solar powered cooler for a smart device such as a smartphone or smart tablet is provided. The cooler may include an upper fan casing, an optional bottom fan casing, smart device holder, and an air passage formed between the upper fan casing and the smart device holder. Also provided are one or more cooling fans drawing air into the air passage along a substantially vertical direction. One or more solar panels allows the cooler to harvest solar energy and deliver electric power to the one or more fans, or motors thereof. The solar panels are connected by one or more, e.g., a pair of, connector cables to the motor. The cooler may cool an entire bottom surface of the smart device using one or more cooling fans.

### Classifications

■ **H02S40/425** Cooling means using a gaseous or a liquid coolant, e.g. air flow ventilation, water circulation

[View 5 more classifications](#)

### Claims

Hide Dependent ^

I claim:

1. A solar powered cooler for a smart device, comprising:
  - an upper fan casing;
  - a bottom fan casing;
  - a smart device holder for holding a smart device;
  - one or more cooling fans effective to draw air into an air passage formed between the upper fan casing and the smart device holder, thereby forcing air to flow along a substantially vertical direction toward a bottom surface of the smart device in a substantially horizontal orientation; and
  - one or more solar panels for harvesting solar energy and delivering electric power to the one or more cooling fans, the one or more solar panels connected to the one or more fans via one or more connector cables.
2. The cooler of claim 1, further comprising a solar panel protector cover having a clear plastic window over the solar panel, the solar panel protector cover secured to the solar panel with snap fastener and insert elements.
3. The cooler of claim 1, wherein the one or more cooling fans are located between the upper fan casing and the bottom fan casing.
4. The cooler of claim 1, wherein at least one fan rotates about a substantially vertical axis.
5. The cooler of claim 1, having one or more vent holes formed in the upper and/or lower fan casing.
6. The cooler of claim 5, wherein the smart device holder contains the smart device in a manner such that air directed toward the bottom surface of the smart device flows horizontally over the bottom surface.
7. The cooler of claim 6, wherein the smart device is attached to the upper fan casing by magnetic means.
8. The cooler of claim 7, wherein the smart device is a smartphone or smart tablet, the solar powered cooler comprising

EP3593607A1

European Patent Office

Publication of application with search report

[Find Prior Art](#)

[Similar](#)

**Other languages:** [German](#), [French](#)

**Inventor:** [Reginald L. WALKER](#)

**Current Assignee :** [Tapicu Inc](#)

### Worldwide applications

2018 [US](#) [CN](#) [EP](#) [KR](#) [JP](#) [WO](#)

### Application EP18763864.8A events

2017-03-06 Priority to US201762600948P

2018-03-04 Priority to US15/911,154

2018-03-05 Application filed by Tapicu Inc

2018-03-05 Priority to PCT/US2018/020950

2020-01-15 Publication of EP3593607A1

**Status** Pending

**Info:** [Patent citations \(9\)](#), [Legal events](#), [Similar documents](#), [Priority and Related Applications](#)

**External links:** [Espacenet](#), [EPO GPI](#), [EP Register](#), [Global Dossier](#), [Discuss](#)

9. A solar powered cooler for a smart device, comprising:

an upper fan casing including one or more vent holes;

a bottom fan casing including one or more air inlet holes located at or near an edge of the bottom fan casing, the upper and bottom fan casing defining an air passage to allow air flow from the one or more air inlet holes to the one or more vent holes;

a smart device holder for holding a smart device;

one or more cooling fans effective to draw air into the air passage so as to force air to flow along a substantially vertical direction through the one or more vent holes toward a bottom surface of the smart device; and

one or more solar panels for harvesting solar energy and delivering electric power to the one or more cooling fans, the one or more solar panels connected to the one or more fans via one or more connector cables.

Publication of application with search report

10. A solar powered cooler for a smart device, comprising:

an upper fan casing including one or more vent holes;

a bottom fan casing including one or more air inlet holes located at or near an edge of the bottom fan casing, the upper and bottom fan casing defining an air passage to allow air flow from the one or more air inlet holes to the one or more vent holes;

a smart device holder for holding a smart device;

one or more cooling fans located between the upper and lower fan casings, the one or more cooling fans covering the one or more air inlet holes effective to draw air into the air passage so as to force air to flow along a substantially vertical direction toward a bottom surface of the smart device; and

one or more solar panels for harvesting solar energy and delivering electric power to the one or more cooling fans, the one or more solar panels connected to the one or more fans via one or more connector cables.

## Description

### SOLAR POWERED COOLER FOR SMART DEVICE

#### BACKGROUND OF THE INVENTION

[0001] Field of the Invention

[0002] The present invention relates generally to fans and, more specifically, to a solar powered cooling unit which provides a housing that can be comfortably hand held. The unit typically has a small, compact, rectangular design that includes a fan and may be easily stored and transported on one's person, in a brief case or beach bag.

[0003] Description of the Prior Art

[0004] There is a need for solar cooling units. For example, a number of solar powered fan devices have been designed for personal cooling or ventilation. Typical of these is U.S. Pat. No. 4,899,645 issued to Wolfe, et al. on Feb. 13, 1990.

[0005] Another patent was issued to Hwang on Nov. 27, 1990 as U.S. Pat. No.

4,974,126. Yet another U.S. Pat. No. 4,986,169 was issued to Chen on Jan. 22, 1991, and still yet another was issued on Sep. 3, 1991 to Wu, et al. as U.S. Pat. No. 5,044,258.

[0006] Another patent was issued to Juang on Sep. 22, 1992 as U.S. Pat. No.

5,148,736. Yet another U.S. Pat. No. 5,250,265 was issued to Kawaguchi, et al. on Oct. 5, 1993. Another was issued to Femg on Dec. 31, 1996 as U.S. Pat. No. 5,588,909, and still yet another was issued on Mar. 7, 2000 to Asenguah, et al. as U. S. Pat. No. 6,032,291.

[0007] Another patent was issued to Sibbe on May 30, 1984 as German Patent No.

DE3337241. Yet another U.K. Patent No. GB2241378 was issued to Forsyth on Aug. 28, 1991. Another was issued to Takahashi on Oct. 3, 1995 as Japan Patent No. JP7253096, and still yet another was issued on Jul. 18, 2003 to Sha as Japan Patent No. JP2003201990.

Another patent was issued to Patel on Jan. 11, 2011 as U.S. Pat. No. 7,866,958.

[0008] There is also a need for holders for smart devices. Typical of these is U.S. Pat.

No. 8,861,714 issued to Leibenhaut et al on Oct. 14, 2014. Another patent was issued to Crome et al. on Apr. 23, 2013 as U.S. Pat. No. 8,428,665. Another patent was issued to Leibenhaut, et al on Oct. 20, 2015 as U.S. Pat. No. 9,167,062. Yet another patent application was submitted by Chu on Sept. 15, 2014 as U.S. Pat. App. Publ. No. 2016/0076547.

[0009] Another patent was issued to An et al on Dec. 13, 2016 as U. S. Pat. No.

9,521,224, and still yet another was issued on Apr. 29, 2014 to Trinh et al as U.S. Pat. No. 8,711,553. [0010] Yet another patent application was submitted by Ross III on Sep. 17, 2009 as

U.S. Pat. App. Publ. No. 2009/0233656. Yet another patent application submitted by

Backman et al on Oct. 18, 2015 as U.S. Pat. App. Publ. No. 2015/0283950.

[0011] There is a further need solar power car ventilators. Typical of these is U.S.

Pat. No. 5,148,736 issued to Juang on Sep. 22 1992 and still yet another was issued on Oct. 8, 2011 to Tamowsky et al as U. S. Pat. No. 8,039,988.

[0012] However, none of the above-identified publications specifically addresses drawbacks associated with the heat generated by battery powered smart devices. Similarly, none of the above-identified publication addresses drawbacks associated with the operation of smart devices in excessively hot environments.

[0013] Thus, opportunities exist to provide an easily carryable fan for smart devices such as smart phone and smart tablets with one or more solar panels, which can be used outdoors with no power supply.

#### SUMMARY OF THE INVENTION

[0014] A first object of the present invention is to provide one or more solar powered fans for smart devices.

[0015] Another object of the present invention is to provide compact rectangular housing that can be comfortably hand held powered by means of one or more solar panels. The intensity of solar energy may work to control power to one or more fan motors.

[0016] A further object of the present invention is to provide a small, portable solar panel to power the one or more fans.

[0017] In a first embodiment, then, a solar powered cooler is provided for a smart device such as a smartphone or smart tablet. The cooler includes an upper fan casing, an optional bottom fan casing, smart device holder, and an air passage formed between the upper fan casing and the smart device holder. The cooler includes one or more cooling fans drawing air into the air passage along a substantially vertical direction. One or more solar panels allows the cooler to draw electric power to the one or more fans, or motors thereof. The solar panels are connected by one or more, e.g., a pair of, connector cables to the motor. Publication of application with search report

[0018] Optionally, a solar panel protector cover may be provided over the solar panel.

The cover may include a clear plastic window and may be secured to the solar panel with snap fastener and insert elements. [0019] Typically, the one or more cooling fans are located between the upper and lower fan casings, and each fan rotate about a substantially vertical axis to draw air into the air passage along the substantially vertical direction. In addition (or in the alternative), one or more cooling fans may rotate about a horizontal axis.

[0020] Thus, one or more vent holes may be formed in the upper and/or lower fan casing. Air drawn in by the one or more cooling fans may be forced through the air passage and discharged through the one or more vent holes in order to cool the bottom surface of a smart device in the smart device holder.

[0021] The smart device holder is typically constructed to containing a smart device such as a smartphone or smart tablet. The holder may have a construction that allows horizontal air flow over a bottom surface of the smart device. Optionally, the holder allows the smart device to be securely attached to the upper fan casing, e.g., by magnetic means.

[0022] In another embodiment, a solar powered cooler similar to the embodiment described above is provided, wherein the upper fan casing including one or more vent holes. The bottom fan casing may include one or more air inlet holes. The upper and lower fan casings define an air passage to allow air to flow from the air inlet holes to the one or more vent holes. The one or more air inlet holes may be located at an edge or near an edge of the bottom fan casing. Air drawn in by the one or more cooling fans may be forced out through the air passage in a horizontal direction and discharged through the one or more vent holes in order to cool the smart device.

[0023] In a further embodiment, a solar powered cooler similar to the embodiment described above is provided, wherein the one or more air inlet holes are located at an edge or near an edge of the bottom fan casing. One or more cooling fans are located on the bottom fan casing covering the one or more air inlet holes, wherein the one or more cooling fans are located between the upper fan casing and the bottom fan casing.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIG. 1 is a perspective view of a single fan solar powered cooler for a smart device such as a smartphone or smart tablet.

[0025] FIG. 2 is an exploded perspective view of the single fan solar powered cooler of FIG. 1 with the corresponding smart device holder.

[0026] FIG. 3 is a top view of a single fan solar powered cooler.

[0027] FIG. 4 is a side view of the single fan solar powered cooler of FIG. 1 with the corresponding smart device holder. [0028] FIG. 5 is a bottom view of the single fan solar powered cooler.

[0029] FIG. 6 is the rear view of the single fan solar powered cooler of FIG. 1 with the corresponding smart device holder.

[0030] FIG. 7 is a side sectional view of the single fan solar powered cooler of FIG. 3 with the corresponding smart device holder along cut lines VII-VII.

[0031] FIG. 8 is a condensed exploded perspective view of the single fan solar powered cooler of FIG. 2.

[0032] FIG. 9 is a perspective view of a dual fan solar powered cooler for a smart device such as a smartphone or smart tablet.

[0033] FIG. 10 is an exploded perspective view of the dual fan solar powered cooler of FIG. 9 with the corresponding smart device holder.

[0034] FIG. 11 is a top view of a dual fan solar powered cooler.

[0035] FIG. 12 is a side view of the dual fan solar powered cooler of FIG. 9 with the corresponding smart device holder.

[0036] FIG. 13 is a bottom view of the dual fan solar powered cooler of FIG. 9 with the corresponding smart device holder.

[0037] FIG. 14 is the rear view of the dual fan solar powered cooler of dual fan solar powered cooler of FIG. 9.

[0038] FIG. 15 is a side sectional view of the dual fan solar powered cooler of FIG. 9.

11 with the corresponding smart device holder along cut lines XIII -XIII.

[0039] FIG. 16 is a condensed exploded perspective view of the dual fan solar powered cooler of FIG. 10.

#### DETAILED DESCRIPTION OF THE INVENTION

[0040] Before describing the present invention in detail, it is to be understood that the invention is not limited to specific separation devices or types of analytical instrumentation, as such may vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting.

[0041] In addition, as used in this specification and the appended claims, the singular article forms "a," "an," and "the" include both singular and plural referents unless the context clearly dictates otherwise. Thus, for example, reference to "a fan" includes a plurality of fans as well as a single fan, reference to a "solar panel" includes a single solar panel as well as a combination of solar panels, and the like. [0042] Furthermore, terminology indicative or suggestive of a particular spatial relationship between elements of the invention is to be construed in a relative sense rather an absolute sense unless the context of usage clearly dictates to the contrary. For example, the

terms "over" and "on" as used to describe the spatial orientation of a first item relative to a second item does not necessarily indicate that the first item is located above the second item. Thus, in a cooler that includes a holder placed on or over a smart device, the holder may be located above, at the same level as, or below the smart device depending on the cooler's orientation. Similarly, an "upper" surface of a smart device may lie above, at the same level as, or below other portions of the device depending on the orientation of the device.

[0043] In this specification and in the claims that follow, reference will be made to a number of terms that shall be defined to have the following meanings, unless the context in which they are employed clearly indicates otherwise:

[0044] The terms "electronic," "electronically," and the like are used in their ordinary sense and relate to structures, e.g., semiconductor microstructures, that provide controlled conduction of electrons, holes and/or other charge carriers.

[0045] "Optional" or "optionally" means that the subsequently described

circumstance may or may not occur, so that the description includes instances where the circumstance occurs and instance [Publication of application with search report](#)

[0046] The term "smart device" is used herein in its ordinary sense and refers to an electronic device, generally connected to other devices or networks via different wireless protocols such as Bluetooth, NFC, Wi-Fi, 3G, etc. , that can operate to some extent interactively and autonomously. Exemplary smart devices include

[0047] The term "solar panel" is used herein in its ordinary sense and refers to a panel designed to absorb sunlight and/or other photonic radiation as a source of energy for generating electricity.

[0048] In general, the invention provides an easily carryable or portable cooler that includes a fan powered by with one or more solar panels. The fan directs air toward a holder for a smart device such as a smart phone or a smart tablet, thereby cooling the smart device. The cooler can be used outdoors with no power supply, and overcomes the shortcomings of the prior art. That is, a solar powered smart device fan is provided with a much broader spectrum of both portable and fixed operating applications, whereas prior art is application specific.

[0049] Turning now descriptively to the drawings, in which like reference numbers denote like elements throughout the several views, various embodiments of the invention are depicted. With regard to the reference numerals used, the following numbering is used throughout the various drawing figures for single fan embodiments of the invention.

18 protective grille for 20 fan blade

20 fan blade

24 protective grille insertion pegs

37 magnet holders for the upper fan casing

37 magnet holder placement peg

40 smart device air flow passage

42 circular vent holes for 60 front fan motor

46 receiving hole for 50 front fan motor spindle

50 fan motor spindle

58 upper fan casing for 60 front fan motor

60 front fan motor

68 electric connector wiring

70 solar panel

71 positive terminal point

72 negative terminal point

74 bottom fan casing

76 transparent cover for 70 solar panel

78 smart device holder

84 magnets for 78 smart device holder

86 upper snap fastener

88 lower snap fastener insert

90 bottom fan casing air inlet in 74 bottom fan casing

94 air passage opening in 78 smart device holder for air flow

95 air flow grooves in 78 smart device holder

[0050] A single fan solar powered cooler for a smart device such as a smartphone or smart tablet is shown in FIGS. 1 through 8. FIG. 1 provides a perspective view of certain assembled components of the single fan solar powered cooler for a smart device. FIG. 2 and FIG. 8 are exploded perspective views of a single fan solar powered cooler for a smart device. The device is magnetically connected to smart device holder 78. The holder 78 incorporates air passage opening 94 corresponding in position and size to the location of the protective grille 18 for fan blade 20 coupled to a fan motor spindle 50 for the front fan motor 60. The protective grille 18 is attached to the upper fan casing 58 using protective grille insertion pegs 24. Air flow is distributed over the bottom surface of a smart device by air flow grooves 95 which are long narrow shapes coupled with the circular air passage opening 94 incorporated in the upper surface of smart device holder 78.

[0051] Thus, FIG. 1, FIG. 2, and FIG. 8 show the single fan solar powered cooler which includes an upper fan casing 58 for front fan motor 60, housing a protective grille 18 for fan blade 20, magnet holders for upper fan casing 34, magnets for the for connecting the smart device holder 36 held in place by magnet holder placement pegs 37, circular vent holes 42 for front fan motor 60, receiving hole 46 for fan motor spindle 50, electric connector wiring 68, solar panel 70, positive terminal point 71, negative terminal point 72. FIG. 5 shows the bottom fan casing 74 providing support for the transparent cover 76 for solar panel 70 and incorporates upper snap fastener 86, lower snap fastener insert 88, and bottom fan casing air inlets 90 in bottom fan casing 78.

[0052] Returning to FIG. 2, circular vent holes 42 for front fan motor 60 are formed in the upper fan casing 58. Smart device air flow passage 40 and circular vent holes 42 for front fan motor 60 corresponding in position and size to the location of the protective grille 18 for fan blade 20 coupled to the fan motor spindle 50 for the front fan motor 60.

[0053] FIG. 7 is a side sectional view along cut line VII-VII of FIG. 3. FIG. 7 illustrates the smart device wherein a single fan solar powered cooler is magnetically connected to smart device holder 78. The air flow within and parallel to smart device such as a smartphone or smart tablet wherein the single fan solar powered cooler is magnetically connected to smart device holder 78 is blown vertically by the fan blade 20 coupled to the fan motor spindle 50 such as a smartphone or smart tablet is cooled by the air flow produced by the fan blade 20 coupled to the fan motor spindle Publication of application with search report

[0054] The single fan solar powered cooler for a smart device addresses specific portions of the bottom surface of the smart device which are to be cooled. That is, the air blown up by the fan blade 20 coupled to the fan motor spindle 50 for the front fan motor 60, which are axial fans, into the smart device holder 78 is directly discharged horizontally through air flow grooves 95 which are long narrow shapes coupled with the circular air passage opening 94. Accordingly, the entire area of the bottom surface of the smart device such as a smartphone or smart tablet is cooled.

[0055] Referring to FIG. 2, FIG. 3, FIG. 4, FIG. 6, FIG. 7 and FIG. 8, air exiting smart device air flow passage 40 and circular vent holes 42 is moved along the bottom surface of the smart device contained within the smart device holder 78, thereby cooling the bottom surface of the smart device. Heat dissipation is carried out at portions of the bottom surface of the smart device with which the air collides. As a result, desired cooling is achieved.

[0056] That is, as shown in FIG. 2, the smart device may be magnetically connected to smart device holder 78 which incorporates air passage opening 94 corresponding in position and size to the location of the protective grille 18 for fan blade 20 coupled to the fan motor spindle 50 for the front fan motor 60 facilitates the continuous vertical alignment of air passage opening 94 with the corresponding protective grille 18 for fan blade 20 coupled to the fan motor spindle 50 for the front fan motor 60. The air passage opening 94 acts as a conduit for guiding air drawn by the fan blade 20 coupled to the fan motor spindle 50 for the front fan motor. The front fan motor 60 are not limited to their positions and number as long as they can blow air into the air passage opening 94. Additionally, a reduction in the height of the front fan motor 60 and the fan motor spindle 50 can reduce the total height of the single fan solar powered cooler for a smart device.

[0057] The single fan solar powered cooler for a smart device constructed as described above can cool the entire bottom surface area of the smart device such as a smartphone or smart tablet by magnetically connecting to smart device holder 78 to the upper fan casing 58. All of the individual components may be glued to their corresponding connecting parts to remain in place, respectively. Additionally, cooling can be achieved as shown in other embodiments such as the dual fan solar powered cooler for a smart device such as a smartphone or smart tablet.

[0058] In sum, in one embodiment of the present invention, air suction openings for single fan solar powered cooler for smart device include air flow passage 40, circular vent holes 42 is formed on the top surface of a housing upper fan casing 58 for front fan motor 60, and bottom fan casing air inlet 90 in bottom fan casing 74. An exhaust opening is formed on the top surface of a housing upper fan casing 58 through protective grille 18 for front fan blade 20 coupled to front fan motor 60 circulating air flow through a smart device holder 78 with an air passage opening 94 and air flow grooves 95 in smart device holder 78 for cooling the bottom surface of the smart device. The solar panel 70 for front fan motor 60 is connected to positive terminal point 71 and negative terminal point 72 using electric connector wiring 68 so that the fan motor may be driven by means of its power generation output. Thus, this portable type solar powered fan can be used simply without any place restrictions. [0059] The following numbering is used throughout the various drawing figures for dual fan embodiments of the invention.

218 front protective grille for 220 front fan blade

228 rear protective grille for 214 rear fan blade

220 front fan blade

214 rear fan blade

224 protective grille insertion pegs

234 magnet holders for upper fan casing

236 magnets for the upper fan casing

237 magnet holder placement peg

240 smart device air flow passage

242 circular vent holes for 260 front fan motor and 266 rear fan motor

246 receiving hole for 250 fan motor spindle

250 fan motor spindle

258 upper fan casing for 260 front fan motor and 266 rear fan motor

260 front fan motor

266 rear fan motor

268 electric connector wiring

270 solar panel

271 positive terminal point

272 negative terminal point

274 bottom fan casing  
276 transparent cover for 270 solar panel  
278 smart device holder  
284 magnets for 278 smart device holder  
286 upper snap fastener  
288 lower snap fastener insert  
290 bottom fan casing air inlet in 274 bottom fan casing  
294 air passage opening in 278 smart device holder for air flow  
295 air flow grooves in 278 smart device holder  
298 air passage opening in 278 smart device holder for air flow

Publication of application with search report

[0060] In another embodiment, the invention provides a dual fan solar powered cooler for a smart device, e.g., as shown in FIGS. 9 through 16. FIG. 9 provides a perspective view of certain assembled components of the dual fan solar powered cooler for a smart device. FIG. 10 and FIG. 16 are exploded perspective views of a dual fan solar powered cooler for a smart device. The device is magnetically connected to smart device holder 278. The holder 278 incorporates air passage opening 294 corresponding in position and size to the location of the front protective grille 218 for front fan blade 220. The holder 278 incorporates air passage opening 298 corresponding in position and size to the location of and rear protective grille 228 for rear fan blade 214. Blade 220 are coupled to the fan motor spindle 250 for the front fan motor 260. The front protective grille 218 and rear protective grille 228 are attached to the upper fan casing 258 using protective grille insertion pegs 224. Air flow is distributed over the bottom surface of smart device by air flow grooves 295 which are long narrow shapes coupled with the circular air passage opening 294 incorporated in the upper surface of smart device holder 278.

[0061] FIG. 10 and FIG. 16 show a dual fan solar powered cooler which includes an upper fan casing 258 for a pair of motors, i.e., front fan motor 260 and rear fan motor 266. Also shown housed by the casing 258 is a front protective grille 218 for front fan blade 220 and a rear protective grille 228 for rear fan blade 214, respectively. Additionally, provided are magnet holders for upper fan casing 234 and magnets for connecting the smart device holder 236, which are held in place by magnet holder placement pegs 237. Further provided are circular vent holes 242 for front fan motor 260 and rear fan motor 266, receiving hole 246 for fan motor spindle 250, electric connector wiring 268, solar panel 270, positive terminal point 271, and negative terminal point 272.

[0062] FIG. 13 shows the bottom fan casing 274 that provides support for the transparent cover 276 for solar panel 270. As shown in FIG. 10, the bottom fan casing 274 also incorporates upper snap fastener 286, lower snap fastener insert 288, and bottom fan casing air inlets 290. Circular vent holes 242 are formed in the upper fan casing 258 for front fan motor 260 and rear fan motor 266. Smart device air flow passage 240 and circular vent holes 242 for front fan motor 260 and rear fan motor 266 correspond in position and size to the location of the front protective grille 218 for front fan blade 220 and rear protective grille 228 for rear fan blade 214, which are coupled to the fan motor spindle 250 for front fan motor 260 and rear fan motor 266, respectively.

[0063] FIG. 15 is a side sectional view along cut line XIII-XIII of FIG. 11 illustrates the smart device wherein the dual fan solar powered cooler is magnetically connected to smart device holder 278. Air flow within and parallel to smart device wherein the dual fan solar powered cooler is magnetically connected to smart device holder 278 is forced perpendicular to the front fan blade 220 and rear fan blade 214 coupled to their fan motor spindle 250 for front fan motor 260 and rear fan motor 266, respectively. The smart device is thereby cooled by the air flow produced by the front fan blade 220 and rear fan blade 214 coupled to their fan motor spindle 250 for front fan motor 260 and rear fan motor 266, respectively.

[0064] As shown FIG. 10 and FIG. 16, the dual fan solar powered cooler for a smart device addresses specific portions of the bottom surface of the smart device which are to be cooled. That is, the air is blown upward by the front fan blade 220 and rear fan blade 214, which are coupled to their fan motor spindle 250 for the front fan motor 260 and rear fan motor 266, respectively. Air from these axial fans is introduced into the smart device holder 278 and directly discharged upward flowing air through air flow grooves 295 which are long narrow shapes coupled with the circular air passage opening 294. Accordingly, the entire area of the bottom surface of the smart device such as a smartphone or smart tablet is cooled.

[0065] Referring to FIG. 11, FIG. 12, FIG. 14, and FIG. 15, the air exiting smart device air flow passage 240 and circular vent holes 242 is moved along the bottom surface of the smart device such as a smartphone or smart tablet contained within the smart device holder 278, thereby cooling the bottom surface of the smart device such as a smartphone or smart tablet. Portions of the bottom surface of the smart device with which the air collides are cooled via heat dissipation. That is, magnetically connected to smart device holder 278 which incorporates air passage opening 294 corresponding in position and size to the location of the front protective grille 218 for front fan blade 220 and rear protective grille 228 for rear fan blade 214. Fan motor spindle 250 for the front fan motor 260 facilitates the continuous vertical alignment of air passage opening 294 with the corresponding front protective grille 218 and rear protective grille 228 coupled to their fan motor spindle 250, respectively. The air passage opening 294 acts as a conduit for guiding air drawn by the front fan blade 220 and rear fan blade 214 coupled to their fan motor spindle 250 for the front fan motor, respectively. The front fan motor 260 and rear fan motor 266, are not limited to their positions and number as long as they can blow air into the air passage opening 294.

Additionally, a reduction in the height of the front fan motor 260 and rear fan motor 266, and their respective fan motor spindle 250 can reduce the total height of the dual fan solar powered cooler for a smart device.

[0066] The dual fan solar powered cooler for a smart device constructed as described above can cool the entire bottom surface area of the smart device such as a smartphone or smart tablet by magnetically connected to smart device holder 278 to the upper fan casing 258. All of the individual components are glued to their corresponding connecting parts to remain in place, respectively.

[0067] In sum, air suction openings for dual fan solar powered cooler for smart device are shown as smart device air flow passage 240. Circular vent holes 242 are formed on top surface of a housing upper fan casing 258 for front fan motor 260 and rear fan motor 266. Bottom fan casing air inlet 290 is located in bottom fan casing 274. An exhaust opening is formed on the top surface of a housing upper fan casing 258 through front protective grille 218 for front fan blade 220 and through rear protective grille 228 for rear fan blade 214, each circulating air flow through a smart device holder 278 with dual air passage openings 294 and 298 with air flow grooves 295 in smart device holder 278 for cooling the bottom surface of the smart device. The solar panel 270 for front fan motor 260 and rear fan motor 266 is connected to positive terminal point 271 and negative terminal point 272 using electric connector wiring 268 so that the fan motors may be driven by means of its power generation output. Thus, this portable type solar powered fan can be used simply without any place restrictions.

[0068] As described above, the invention allows air to uniformly collide with a bottom surface of a smart device such as a smartphone or smart tablet. As a result, the invention provides more effectively cooling of the smart device when compared conventional implementations of fans in combination with smart devices.

[0069] The invention may exhibit a number of other advantages as well. For example, wind produced by the fan is typically effective to cool excessive temperatures, and may be directly and personally used by individual away from their usual premises and without any power mains supply available (for example train compartment etc.). That is, individuals may wish to protect themselves from or to alleviate excessive temperatures or their unpleasant attendant manifestations (including perspiration) through the use of the invention. Prior art fans are fundamentally unsuitable for this because they are generally too large and bulky and/or because they do not have an independent power supply. That is, they are tied to buildings.

[0070] In contrast, the invention provides a light, handy design and is equipped with built-in and independent power supply facilities. These independent electrical energy sources in particular may comprise an accumulator, with a charging device and a mains connection, a storage battery, also with a charging device and a mains connection, a dry battery and last but not least solar power on the basis of the photo-voltaic effect.

[0071] The invention may also help prevent smart devices from overheating, or catching on fire. Some prior art devices are fundamentally unsuitable for external use outside of a motor vehicles air conditioning vent.

[0072] Variations of the invention are possible. For example, multiple solar panels can be used for two or more fan motors, in [Publication of application with search report](#) these. Such panels may be formed from a plurality of photovoltaic cells immobilized relative to the smart device. The cells form a solar panel that converts sunlight and other photonic radiant energy electric power. Similarly, in some embodiments, at least one blowing fan and at least one exhaust fan and electrically connected to the output terminals of the electric connector.

[0073] It is to be understood that, while the invention has been described in conjunction with the preferred specific embodiments thereof, the foregoing description merely illustrates and does not limit the scope of the invention. Numerous alternatives and equivalents exist which do not depart from the invention set forth above. For example, any particular embodiment of the invention, e.g., those depicted in any drawing herein, may be modified to include or exclude features of other embodiments. Other aspects, advantages, and modifications within the scope of the invention will be apparent to those skilled in the art to which the invention pertains.

## Patent Citations (9)

Publication number	Priority date	Publication date	Assignee	Title
Family To Family Citations				
<a href="#">KR100739783B1</a> *	2006-01-04	2007-07-13	삼성전자주식회사	Cradle for portable electronic appliance and portable electronic appliance set with the same
<a href="#">US8051904B1</a> *	2007-05-23	2011-11-08	Michael Whiting	Vehicular temperature control device
<a href="#">US7782613B2</a> *	2008-03-19	2010-08-24	Harris Technology, Llc	Cooling system for a portable device
<a href="#">CN201449588U</a> *	2009-06-17	2010-05-05	蔡永坚	Radiating pad seat for laptop computer
<a href="#">TWI465185B</a> *	2012-04-25	2014-12-11	Sunonwealth Electr Mach Ind Co	Cooling system for portable communication device
<a href="#">CN103812981A</a> *	2012-11-14	2014-05-21	鸿富锦精密工业(深圳)有限公司	Mobile phone heat dissipating device
<a href="#">CN203135945U</a> *	2012-12-05	2013-08-14	董伟	Multifunctional cellphone protective casing
<a href="#">CN205883330U</a> *	2016-07-15	2017-01-11	杨诚俊	Forced air cooling cell -phone heat abstractor
<a href="#">CN106331230A</a> *	2016-07-23	2017-01-11	沈攀	Multifunctional detachable modular mobile phone shell

\* Cited by examiner, † Cited by third party

## Similar Documents

Publication	Publication Date	Title
<a href="#">CN103988592B</a>	2017-08-04	Regulator cubicle with the improved dissipation of heat
<a href="#">KR100802767B1</a>	2008-02-12	Cooling system for a battery and motor control unit of a hybrid vehicle
<a href="#">TWI512442B</a>	2015-12-11	A cooling system of hand-held electronic device
<a href="#">ES2270713B1</a>	2008-03-16	Internal ventilation structure for a battery housing to control the temperature inside.
<a href="#">US9719692B2</a>	2017-08-01	Building ventilation system
<a href="#">US8864447B1</a>	2014-10-21	Low-profile, ceiling-mounted fan
<a href="#">JP2004537708A</a>	2004-12-16	Thermoelectric personal environment adjustment equipment
<a href="#">EP1785675A1</a>	2007-05-16	Ventilation arrangements
<a href="#">US7331064B1</a>	2008-02-19	Ventilated cap apparatus
<a href="#">US8375936B2</a>	2013-02-19	Method and system for operating a thermal solar system using a reverse motor configuration
<a href="#">US8291866B2</a>	2012-10-23	Heating and cooling system for pet enclosures

CA2423100C	2006-09-05	Air feeding apparatus
US8051904B1	2011-11-08	Vehicular temperature control device
HU0402251A2	2005-02-28	Solar collector panel for heating ventilation air
US20050168191A1	2005-08-04	Handheld electronic device cradle with enhanced heat-dissipating capability
US20130328359A1	2013-12-12	Ventilation and Cooling System for an Office Chair
BRPI0409399A	2006-04-18	high efficiency thermoelectric water generating device
US6963488B1	2005-11-08	Device to convey the cool air from an air-conditioner into a computer
US20090118869A1	2009-05-07	Heating and cooling system for pet enclosures <span style="float: right;">Publication of application with search report</span>
EP3417915A1	2018-12-26	Energy storage system and fire management method for energy storage system
US20080060586A1	2008-03-13	Portable and adaptable animal cage, crate, kennel and mat air conditioning device: Kool Kennel & Kool Kushion
US20070283961A1	2007-12-13	Air purifier for a protective garment
TWM309144U	2007-04-01	Accommodation box of hard disk with cooling device
US9683752B2	2017-06-20	Hybrid fan assembly and active heating pumping system
JP2012007597A	2012-01-12	Portable fan

## Priority And Related Applications

### Priority Applications (3) ▲

Application	Priority date	Filing date	Title
US201762600948P	2017-03-06	2017-03-06	US Provisional Application
<a href="#">US15/911,154</a>	2017-03-06	2018-03-04	Solar powered cooler for smart device
<a href="#">PCT/US2018/020950</a>	2017-03-06	2018-03-05	Solar powered cooler for smart device

### Legal Events ▲

Date	Code	Title	Description
2020-01-15	17P	Request for examination filed	<b>Effective date:</b> 20191002
2020-01-15	AK	Designated contracting states	<b>Kind code of ref document:</b> A1 <b>Designated state(s):</b> AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
2020-01-15	AV	Request for validation of the european patent	<b>Extension state:</b> KH MA MD TN
2020-01-15	AX	Request for extension of the european patent	<b>Extension state:</b> BA ME
2020-06-10	DAV	Request for validation of the european patent (deleted)	
2020-06-10	DAX	Request for extension of the european patent (deleted)	

### Concepts ▲

[machine-extracted](#)

[Download](#) [Filter table](#) ▼

Name	Image	Sections	Count	Query match
● cooling		claims,abstract,description	28	0.000
● hole materials		claims,description	38	0.000
● fastener		claims,description	10	0.000
● protector		claims,description	3	0.000
● harvesting		claims	3	0.000



[Show all concepts from the description section](#)

Data provided by IFI CLAIMS Patent Services

---

[About](#) [Send Feedback](#) [Public Datasets](#) [Terms](#) [Privacy Policy](#)

Publication of application with search report